

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** EJOT UK Ltd  
Hurricane Close  
Sherburn-in-Elmet  
Leeds  
LS25 6PB  
**Tel:** +44(0)1977 687040  
**Fax:** +44(0)1977 687041  
**Email:** [info@ejot.co.uk](mailto:info@ejot.co.uk)

#### 1.4. Emergency telephone number

**Emergency tel:** Medical emergency information for poisoning:  
Poison Information Centre Mainz - 24h - Tel.: +49 (0) 6131 19240  
(advice in German or English)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Aquatic Chronic 2: H411; Muta. 2: H341; Skin Corr. 1B: H314; Skin Sens. 1: H317; -: EUH208

**Most important adverse effects:** Contains 4,4'-isopropylidenediphenol. May produce an allergic reaction. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** \* EUH208: Contains 4,4'-isopropylidenediphenol. May produce an allergic reaction.  
H314: Causes severe skin burns and eye damage.  
H317: May cause an allergic skin reaction.  
H341: Suspected of causing genetic defects.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS05: Corrosion

# SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 2

GHS07: Exclamation mark

GHS08: Health hazard

GHS09: Environmental



**Signal words:** Danger

**Precautionary statements:** P202: Do not handle until all safety precautions have been read and understood.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

**Haz. ingredients (label):** BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}; BISPHENOL-F EPICHLORHYDRIN RESIN: MW<700; 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; PHENOL

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### \* Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} - REACH registered number(s): 01-2119456619-26-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	30-40%

BISPHENOL-F EPICHLORHYDRIN RESIN: MW<700

-	9003-36-5	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411	10-20%
---	-----------	---	--	--------

1,6-HEXANDIOLDIGLYCIDYLETHER - REACH registered number(s): 01-2119463471-41-0005

240-260-4	16096-31-4	-	Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	10-20%
-----------	------------	---	--	--------

[cont...]

## SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 3

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE - REACH registered number(s): 01-2119514687-32-XXXX

220-666-8	2855-13-2	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	3-10%
-----------	-----------	---	--	-------

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH PHENOL AND M-PHENYLENEBIS(METHYLAMINE)

500-137-0	57214-10-5	-	Skin Corr. 1C: H314; Eye Dam. 1: H318; Skin Sens. 1B: H317; Aquatic Chronic 3: H412	3-10%
-----------	------------	---	---	-------

FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 4,4'-ISOPROPYLIDENEDIPHENOL AND DIETHYLENETRIAMINE

500-263-6	77138-45-5	-	Skin Corr. 1B: H314; Skin Sens. 1: H317; Eye Dam. 1: H318	3-10%
-----------	------------	---	--	-------

ALKYL ESTER REF 722 43/00/2012.0028

-	-	-	Eye Irrit. 2: H319	3-10%
---	---	---	--------------------	-------

1,3-BENZENEDIMETHANAMINE - REACH registered number(s): 01-2119480150-50

216-032-5	1477-55-0	-	Skin Corr. 1B: H314; Aquatic Chronic 3: H412; Acute Tox. 4: H302; Skin Sens. 1: H317; Acute Tox. 3: H331	3-10%
-----------	-----------	---	--	-------

BENZYL ALCOHOL - REACH registered number(s): 01-2119492630-38

202-859-9	100-51-6	-	Acute Tox. 4: H332; Acute Tox. 4: H302	1-3%
-----------	----------	---	--	------

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

202-013-9	90-72-2	-	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-3%
-----------	---------	---	--	------

2,2'-IMINODIETHYLAMINE

203-865-4	111-40-0	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317	1-3%
-----------	----------	---	---	------

PHENOL - REACH registered number(s): 01-2119471329-32-XXXX

203-632-7	108-95-2	-	Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Skin Corr. 1B: H314	<1%
-----------	----------	---	--	-----

4,4'-ISOPROPYLIDENEDIPHENOL

201-245-8	80-05-7	-	Repr. 1B: H360F; STOT SE 3: H335; Eye Dam. 1: H318; Skin Sens. 1: H317	<1%
-----------	---------	---	--	-----

### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 4

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** No data available.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS.  
Do not create dust. Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 13 of SDS.

## Section 7: Handling and storage

[cont...]

# SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 5

## 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Avoid the formation or spread of dust in the air.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

## 7.3. Specific end use(s)

**Specific end use(s):** Building and construction work (SU19).

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

#### 2,2'-IMINODIETHYLAMINE

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	4.3 mg/m <sup>3</sup>	-	-	-

#### PHENOL

UK	2 ppm	4 ppm	-	-
----	-------	-------	---	---

#### 4,4'-ISOPROPYLIDENEDIPHENOL

UK	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	-	-
----	---------------------	---------------------	---	---

### DNEL/PNEC Values

**Hazardous ingredients:**

#### 1,6-HEXANDIOLDIGLYCIDYLETHER

Type	Exposure	Value	Population	Effect
DNEL	Dermal	2.8 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	4.9 mg/m <sup>3</sup>	Workers	Systemic
PNEC	Fresh water	0.0115 mg/l	-	-
PNEC	Fresh water sediments	0.283 mg/kg	-	-
PNEC	Marine water	0.00115 mg/l	-	-
PNEC	Marine sediments	0.0283 mg/kg	-	-
PNEC	Soil (agricultural)	0.223 mg/kg	-	-

#### 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	20.1 mg/m <sup>3</sup>	Workers	Systemic

[cont...]

# SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 6

DNEL	Inhalation	20.1 mg/m <sup>3</sup>	Workers	Local
DNEL	Oral	0.526 mg/kg bw/day	Consumers	Systemic
PNEC	Marine water	0.006 mg/l	-	-

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

**Hand protection:** Protective gloves. Nitrile gloves. Viton gloves. Recommended thickness of material >0.4 mm. Breakthrough time of the glove material > 8 hours. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** No special requirement.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Various

**Odour:** Perceptible odour

**Solubility in water:** Insoluble

**Relative density:** 1.44

### 9.2. Other information

**Other information:** Solid suspension - classified as non-flammable according to results from Test N.1 test method for readily combustible solids.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

[cont...]

# SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 7

## 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

#### 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

ORAL	RAT	LD50	1030	mg/kg
------	-----	------	------	-------

#### 1,3-BENZENEDIMETHANAMINE

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	930	mg/kg
VAPOURS	RAT	LD50	11	mg/kg

#### BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

#### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

ORL	RAT	LD50	1200	mg/kg
SKN	RAT	LD50	1280	mg/kg

#### 2,2'-IMINODIETHYLAMINE

IPR	RAT	LD50	74	mg/kg
ORL	MUS	LD50	970	mg/kg
ORL	RAT	LD50	970	mg/kg

[cont...]

# SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 8

## PHENOL

ORL	MUS	LD50	270	mg/kg
ORL	RAT	LD50	317	mg/kg
SCU	RAT	LD50	460	mg/kg

## 4,4'-ISOPROPYLIDENEDIPHENOL

ORL	MUS	LD50	2400	mg/kg
ORL	RAT	LD50	3250	mg/kg

### Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
Germ cell mutagenicity	--	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** No data available.

**Other information:** Not applicable.

### Section 12: Ecological information

#### 12.1. Toxicity

**Ecotoxicity values:** No data available.

#### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

#### 12.4. Mobility in soil

**Mobility:** Insoluble in water. Heavier than water.

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

[cont...]



# SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 9

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN3259

### 14.2. UN proper shipping name

**Shipping name:** AMINES, SOLID, CORROSIVE, N.O.S.  
(3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE; 2,2'-IMINODIETHYLAMINE;  
1,3-BENZENEDIMETHANAMINE; FORMALDEHYDE, OLIGOMERIC REACTION  
PRODUCTS WITH 4,4'-ISOPROPYL)

### 14.3. Transport hazard class(es)

**Transport class:** 8 (9)

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** Yes

### 14.6. Special precautions for user

**Tunnel code:** E

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No

[cont...]

## SAFETY DATA SHEET

EJOT SUPER EPOXY SE 800 SEISMIC PN: 9570000385

Page: 10

2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH208: Contains 4,4'-isopropylidenediphenol. May produce an allergic reaction.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H341: Suspected of causing genetic defects.

H360F: May damage fertility.

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.